



7018 Differential Pressure Calibrator

Time Electronics

Calibration, Test & Measurement

- Differential range options from 0.2 to 10 bar
- Best accuracy 0.04% of full scale
- Pneumatic
- Over- pressure alarm
- Piezo - resistive pressure sensor
- Isolated 24/36V loop supply
- Loop current measure
- Mains / Battery Power



Options:



40 bar pneumatic hand pump



700 bar hydraulic hand pump



7006 Loop-Mate

From our range of rugged portable pressure calibrators designed for applications from 0.2 bar up to 600 bar, the 7018 differential calibrator covers DP from 0.2 bar to 10 bar in four ranges - specify when ordering the DP and static line pressures, The optional 7090 Pneumatic hand pump can be used as a pressure source covering the range -950 mbar to 40 bar, see separate datasheet.

Also available is a single channel pressure calibrator the 7010, complemented by a dual channel version; the 7015, see separate data sheets. Alternatively, when external line pressures are available the 7010 can be supplied with an internal regulator to control the output pressure - see separate 7016 LPR datasheet.

For process signal calibration the loop signal is displayed on the LCD display to 0.05% accuracy. Loop drive supply (24V or 36V) is also provided. Both pressure and loop signal can be displayed at the same time to speed up the calibration of pressure transmitters. Additionally a continuity function is available for testing for open circuit loops.

The 7018 allows switch selection of four pressure units. These should be specified on ordering from the following:- bar, PSI, kPa, cmWg, inHg, mmHg, Kg/cm².

Both pressure and loop current are displayed on a 4.5 digit LCD switchable back lit display.

RS232 connection for display read-back when used with Time Electronics EasyCal calibration software (option). Straightforward calibration procedures are easy for the user to write within EasyCal. Results from procedures are stored in EasyCal's results database and printing calibration certificates on demand is simple.

Power is via internal rechargeable cells with a built in mains charger. This allows the unit to be powered directly from the mains if required. The 7018 is housed in a strong resin case that provides on-site protection. All pressure connections are inside the case mounted on the top panel. Leads and an assortment of pressure connection accessories are provided.

For process control signal simulation Time Electronics' handheld 7006 Loop-Mate is available as an option. It provides 4 - 20mA and 0 - 10V signals at levels of 0%, 10%, 25%, 50%, 75%, 90%, 100%. It can also step through these set points automatically to allow hands free calibration. It is battery powered and can be stored in the 7018's pouch. Please see separate datasheet for more information.

7018 Technical Specifications

Pressure

Range (bar)	Vacuum	0.2	2	5	10
Resolution (bar)	.0001	0.01mb	.0001	0.001	0.001
Acc. % +/-1 digit	0.04	0.1	0.04	0.04	0.04
Temp Stability:	Less than 70 ppm per °C				
Units:	bar, PSI, kPa, cmWg, inHg, mmHg, Kg/cm2, **				
Max Pressure:	2 x range, 1.5 x range for 20 bar and above				
Max Static Pressure:	20bar				
Sensor:	Piezo-resistive - stainless steel diaphragm				
Over press warning:	1.2 x range full scale - audio and visual (on LCD) warning				
Fittings:	Minimess (>20 bar) & Quick Release (<20 bar)				
	** Specify on ordering: 4 off				

Electrical

Range:	Loop current measurement 0 - 200 mA
Resolution:	10 µA
Resistance:	Loop load 5 ohm
Accuracy:	0.05% of reading ±1 digit
Loop Drive:	24V or 36V switch selectable, 50 mA max - isolated and with short circuit protection
Continuity:	Threshold: 100 ohms with audio and visual warning
RS232:	3.5mm Stereo socket
Terminals:	4 mm industry standard terminal posts

General Specification

Power Source:	Internal rechargeable Nickel Metal Hydride batteries, or mains supply (230V or 110V 50/60 Hz)
Battery Life:	24 hrs of typical usage
Display:	7 segment LCD with 'Low Battery' warning indicator
RS232:	For Read-back (Software not supplied) and re-calibration with supplied software via PC (not supplied)
Case:	Structural resin which is weather-proof to IP 66 standard
Size / Weight:	27 x 25 x 17.5 cm (11" x 10" x 7"), approx 3 kg (6.5 lbs) <i>Unit comes supplied with test leads</i>

Ordering Information

Code	Description
7018	Pressure Calibrator differential (+ differential + static pressures + pressure units required)
7090	Pneumatic hand pump –950mB to40 bar
7095	Hydraulic Pressure Calibration pump 0 to 700bar
7006	Loop-Mate loop current simulator
9747	EasyCal Software (Automatic Calibration Software, including over 1000 procedures)
9178	N.P.L. Traceable Calibration Certificate
9190	UKAS Calibration Certificate

Due to continuous development Time Electronics reserves the right to change specifications without prior notice.

Time Electronics, Botany Industrial Est. Tonbridge, Kent. England. TN9 1RH.
Tel: +44 (0)1732 355993 Fax: +44 (0)1732 770312 E-mail: mail@timeelectronics.co.uk

www.timeelectronics.co.uk

V1b 07/08/08